

Product data sheet

Characteristics

LC1G2654KUEN

High power contactor, TeSys Giga, 4 pole (4NO), AC-1 $\leq 440\text{V}$ 385A, standard version, 100...250V wide band AC/DC coil



Main

Range	TeSys
Range of product	TeSys Giga
Product or component type	Contactor
Device short name	LC1G
Contactor application	Power switching
Utilisation category	AC-3 AC-3e AC-1 AC-5a AC-5b AC-6a AC-6b DC-1 DC-3 DC-5
Poles description	4P
[Ue] rated operational voltage	$\leq 1000\text{ V AC 50/60 Hz}$ $\leq 460\text{ V DC}$
[Ie] rated operational current	265 A (at $<60\text{ }^{\circ}\text{C}$) at $\leq 440\text{ V AC-3}$ 385 A (at $<40\text{ }^{\circ}\text{C}$) at $\leq 1000\text{ V AC-1}$
[Uc] control circuit voltage	100...250 V AC 50/60 Hz 100...250 V DC
Control circuit voltage limits	Operational: 0.8 Uc Min...1.1 Uc Max (at $<60\text{ }^{\circ}\text{C}$) Drop-out: 0.1 Uc Max...0.45 Uc Min (at $<60\text{ }^{\circ}\text{C}$)

Complementary

[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	385 A (at $40\text{ }^{\circ}\text{C}$)
Rated breaking capacity	2380 A at 440 V
[Icw] rated short-time withstand current	2.2 KA - 10 s 1.23 KA - 30 s 0.95 KA - 1 min 0.62 KA - 3 min 0.48 KA - 10 min
Associated fuse rating	315 A aM at $\leq 440\text{ V}$ for motor 250 A aM at $\leq 690\text{ V}$ for motor 400 A gG at $\leq 690\text{ V}$
Average impedance	0.000144 Ohm
[Ui] rated insulation voltage	1000 V
Power dissipation per pole	20 W AC-1 - Ith 385 A 11 W AC-3 - Ith 265 A
Compatibility code	LC1G
Pole contact composition	4 NO
Auxiliary contact composition	1 NO + 1 NC
Irms rated making capacity	3320 A at 440 V
Coil technology	Built-in bidirectional peak limiting
Mechanical durability	8 Mcycles
Inrush power in VA (50/60 Hz, AC)	700 VA
Inrush power in W (DC)	645 W

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Hold-in power consumption in VA (50/60 Hz, AC)	15.0 VA
Hold-in power consumption in W (DC)	9.1 W
Operating time	40...70 ms closing 15...50 ms opening
Maximum operating rate	600 Cyc/H AC-3 600 Cyc/H AC-3e 300 cyc/h AC-1
Connections - terminals	Power circuit: bar 2 - busbar cross section: 32 x 10 mm Power circuit: lugs-ring terminals 1 185 mm ² Control circuit: push-in 1 0.2...2.5 mm ² - cable stiffness: solid stranded without cable end Control circuit: push-in 1 0.25...2.5 mm ² - cable stiffness: flexible with cable end Control circuit: push-in 2 0.5...1.0 mm ² with cable end Control circuit: push-in 0.75...2.5 mm ² - cable stiffness: solid stranded without cable end Control circuit: push-in 0.75...2.5 mm ² - cable stiffness: flexible with cable end
Connection pitch	45 mm
Mounting support	Plate
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 JIS C8201-5-1
Product certifications	CB Scheme[RETURN]CCC[RETURN]cULus[RETURN]EAC[RETURN]CE[RETURN]UKCA[RETURN] RO-MR by DNV-GL
Tightening torque	35 N.m
Height	225 mm
Width	185 mm
Depth	226 mm
Net weight	8.2 kg

Environment

IP degree of protection	IP2X front face with shrouds conforming to IEC 60529 IP2X front face with shrouds conforming to VDE 0106
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-60...80 °C
Mechanical robustness	Vibrations 5...300 Hz 2 gn contactor open Vibrations 5...300 Hz 4 gn contactor closed Shocks 10 gn 11 ms contactor open Shocks 15 gn 11 ms contactor closed
Colour	Dark grey
Protective treatment	TH
Permissible ambient air temperature around the device	-40...70 °C at Uc

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.5 cm
Package 1 Width	31.0 cm
Package 1 Length	32.0 cm
Package 1 Weight	9.072 kg
Unit Type of Package 2	S06
Number of Units in Package 2	4
Package 2 Height	45 cm
Package 2 Width	60 cm
Package 2 Length	80 cm
Package 2 Weight	46.288 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

