

Product data sheet

Characteristics

LC1G800EHEN

High power contactor, TeSys Giga, 3 pole (3NO), AC-3 $\langle I_t \rangle = 440V$ 800A, standard version, 48...130V wide band AC/DC coil



Main

Range	TeSys
Range of product	TeSys Giga
Product or component type	Contactor
Device short name	LC1G
Contactor application	Power switching Motor control
Utilisation category	AC-1 AC-3 AC-3e AC-4 AC-5a AC-5b AC-6a AC-6b AC-8b AC-8a DC-1 DC-3 DC-5
Poles description	3P
[Ue] rated operational voltage	≤ 1000 V AC 50/60 Hz ≤ 460 V DC
[Ie] rated operational current	1050 A (at <40 °C) at ≤ 1000 V AC-1 800 A (at <60 °C) at ≤ 440 V AC-3
[Uc] control circuit voltage	48...130 V AC 50/60 Hz 48...130 V DC
Control circuit voltage limits	Operational: 0.8 Uc Min...1.1 Uc Max (at <60 °C) Drop-out: 0.1 Uc Max...0.45 Uc Min (at <60 °C)

Complementary

[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	1050 A (at 40 °C)
Rated breaking capacity	5870 A at 440 V
[Icw] rated short-time withstand current	5.5 KA - 10 s 4.6 KA - 30 s 3.6 KA - 1 min 2.6 KA - 3 min 1.7 KA - 10 min
Associated fuse rating	800 A aM at ≤ 440 V for motor 630 A aM at ≤ 690 V for motor 1250 A gG at ≤ 690 V
Average impedance	0.000065 Ohm
[Ui] rated insulation voltage	1000 V
Power dissipation per pole	70 W AC-1 - Ith 1050 A 42 W AC-3 - Ith 800 A
Compatibility code	LC1G
Pole contact composition	3 NO
Auxiliary contact composition	1 NO + 1 NC

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Motor power kW	200 KW at 230 V AC 50/60 Hz (AC-3e) 335 KW at 400 V AC 50/60 Hz (AC-3e) 355 KW at 415 V AC 50/60 Hz (AC-3e) 375 KW at 440 V AC 50/60 Hz (AC-3e) 425 KW at 500 V AC 50/60 Hz (AC-3e) 560 KW at 690 V AC 50/60 Hz (AC-3e) 450 KW at 1000 V AC 50/60 Hz (AC-3e) 250 KW at 230 V AC 50/60 Hz (AC-3) 450 KW at 400 V AC 50/60 Hz (AC-3) 450 KW at 415 V AC 50/60 Hz (AC-3) 450 KW at 440 V AC 50/60 Hz (AC-3) 500 KW at 500 V AC 50/60 Hz (AC-3) 560 KW at 690 V AC 50/60 Hz (AC-3) 450 KW at 1000 V AC 50/60 Hz (AC-3) 200 KW at 230 V AC 50/60 Hz (AC-4) 375 KW at 400 V AC 50/60 Hz (AC-4) 355 KW at 415 V AC 50/60 Hz (AC-4) 375 KW at 440 V AC 50/60 Hz (AC-4) 400 KW at 500 V AC 50/60 Hz (AC-4) 475 KW at 690 V AC 50/60 Hz (AC-4) 400 kW at 1000 V AC 50/60 Hz (AC-4)
Motor power hp	300 Hp at 200/208 V 60 Hz 350 Hp at 230/240 V 60 Hz 700 Hp at 460/480 V 60 Hz 800 hp at 575/600 V 60 Hz
Irms rated making capacity	7640 A at 440 V
Coil technology	Built-in bidirectional peak limiting
Mechanical durability	5 Mcycles
Inrush power in VA (50/60 Hz, AC)	990 VA
Inrush power in W (DC)	790 W
Hold-in power consumption in VA (50/60 Hz, AC)	18.7 VA
Hold-in power consumption in W (DC)	9.5 W
Operating time	40...70 ms closing 15...50 ms opening
Maximum operating rate	600 Cyc/H AC-3 600 Cyc/H AC-3e 300 Cyc/H AC-1 150 cyc/h AC-4
Connections - terminals	Power circuit: bar 2 - busbar cross section: 52 x 20 mm Power circuit: lugs-ring terminals 1 185 mm ² Power circuit: bolted connection Control circuit: push-in 1 0.2...2.5 mm ² - cable stiffness: solid stranded without cable end Control circuit: push-in 1 0.25...2.5 mm ² - cable stiffness: flexible with cable end Control circuit: push-in 2 0.5...1.0 mm ² with cable end Control circuit: push-in 0.75...2.5 mm ² - cable stiffness: solid stranded without cable end Control circuit: push-in 0.75...2.5 mm ² - cable stiffness: flexible with cable end
Connection pitch	70 mm
Mounting support	Plate
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 JIS C8201-5-1
Product certifications	CB Scheme[RETURN]CCC[RETURN]cULus[RETURN]EAC[RETURN]CE[RETURN]UKCA[RETURN] RO-MR by DNV-GL
Tightening torque	58 N.m
Height	284 mm
Width	211 mm
Depth	266 mm
Net weight	14.2 kg

Environment

IP degree of protection	IP2X front face with shrouds conforming to IEC 60529 IP2X front face with shrouds conforming to VDE 0106
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-60...80 °C
Mechanical robustness	Vibrations 5...300 Hz 2 gn contactor open Vibrations 5...300 Hz 4 gn contactor closed Shocks 10 gn 11 ms contactor open Shocks 15 gn 11 ms contactor closed
Colour	Dark grey
Protective treatment	TH
Permissible ambient air temperature around the device	-40...70 °C at Uc

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.000 cm
Package 1 Width	34.000 cm
Package 1 Length	51.000 cm
Package 1 Weight	16.158 kg
Unit Type of Package 2	S06
Number of Units in Package 2	2
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	42.316 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
RoHS exemption information	<input checked="" type="checkbox"/> Yes
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
Circularity Profile	<input checked="" type="checkbox"/> End Of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

