



Main

| | |
|---------------------------|-------------------|
| Range of product | PacDrive 3 |
| Product or component type | Motion controller |

Complementary

| | |
|--|---|
| Product compatibility | LMC101 |
| Number of axis | 4 |
| Discrete input number | 8 for digital input conforming to IEC 61131-2 Type 1 4 for touch probe input conforming to IEC 61131-2 Type 1 |
| Discrete input voltage | 15...30 V - 3...5 V |
| Discrete input voltage type | DC |
| Discrete input current | 4 mA for digital input |
| Anti bounce filtering | 100 µs...4.29 s configurable digital input 100 µs...4.29 s configurable touch probe input 100 µs...4.29 s configurable interrupt input |
| Maximum cable distance between devices | <50 m |
| Discrete output number | 8 digital output |
| Discrete output current | 500 mA for digital output |
| Maximum leakage current | 0.5 mA |
| Maximum number of I/O expansion module | 1 |
| [Us] rated supply voltage | 24 V DC |
| Power consumption in W | 30 W |
| Memory type | 512 MB RAM DDR2 128 kB NVRAM |
| Programming language | IL (instruction list) CFC (continuous function chart) SFC (sequential function chart) LD (ladder) ST (structured text) FBD (function block diagram) |
| Integrated connection type | 2 Ethernet port, connector RJ45 for protocol Sercos 1 Ethernet port, connector RJ45 for protocol Ethernet 10/100BASE-T, FTP/HTTP 1 Ethernet port, connector RJ45 for master encoder 1 serial link, connector RJ45 for protocol RS232/RS485 1 CAN port, connector SUB-D 9 for protocol CANopen 1 USB port, connector USB type A |
| Supply | Power supply: 24 VDC |
| Width | 44 mm |
| Height | 270 mm |
| Depth | 222 mm |
| Net weight | 2.2 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|--|
| Standards | UL 508 CSA C22.2 No 142 CSA C22.2 No 14 EN/IEC 61131-2 |
| Product certifications | EAC[RETURN]CE[RETURN]cULus[RETURN]CSA |
| Ambient air temperature for operation | 5...55 °C |
| Relative humidity | 5...95 % without condensation |
| IP degree of protection | IP20 conforming to EN/IEC 60529 |
| Pollution degree | 2 conforming to IEC 61131-2 |
| Operating altitude | 0...2000 m |
| Vibration resistance | 3.5 mm at 5...8.4 Hz 10 m/s ² at 8.4...150 Hz |
| Shock resistance | 150 m/s ² for 6 ms (operation) conforming to EN/IEC 60721-3-3 |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 10.600 cm |
| Package 1 Width | 33.000 cm |
| Package 1 Length | 44.000 cm |
| Package 1 Weight | 2.210 kg |
| Unit Type of Package 2 | P06 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 75.000 cm |
| Package 2 Width | 60.000 cm |
| Package 2 Length | 80.000 cm |
| Package 2 Weight | 32.100 kg |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|