

Product data sheet

Characteristics

LV432465

Earth-leakage VigiPacT add-on protection module, ComPacT NSX 400/630, 200VAC to 440VAC, 30mA to 30A, 4 poles



Main

| | |
|--|--|
| Range of product | ComPacT NSX400...630 new generation ComPacT NSX400...630 |
| Device short name | VigiPacT |
| Product or component type | Vigi add-on |
| Device application | Wiring |
| Range compatibility | ComPacT new generation ComPacT NSX400 new generation circuit breaker ComPacT new generation ComPacT NSX630 new generation circuit breaker ComPacT ComPacT NSX400 circuit breaker ComPacT ComPacT NSX630 circuit breaker |
| Poles description | 4P |
| [In] rated current | 400 A 630 A |
| Earth-leakage protection class | Class A Class AC |
| Residual earth-leakage sensitivity adjustment type | Adjustable |
| Earth-leakage sensitivity | 0.03 A for class A 0.1 A for class A 0.3 A for class A 0.5 A for class A 1 A for class A 3 A for class A 10 A for class AC 30 A for class AC |
| Residual earth-leakage time delay adjustment type | Adjustable |
| [Δt] residual earth-leakage time delay adjustment | 0 Ms 60 Ms 150 Ms 300 Ms 500 Ms 800 Ms 1.2 S 4 s |

Complementary

| | |
|--------------------------------|---|
| Network type | AC |
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | 200...440 V AC 50/60 Hz conforming to IEC 60947-2 |
| Earth-leakage protection | With |
| Maximum breaking time | 800 ms |
| Overshoot category | IV |

Environment

| | |
|-----------------------------------|-------------|
| Electrical shock protection class | Class II |
| Standards | IEC 60947-2 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or intended user to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 14.000 cm |
| Package 1 Width | 17.200 cm |
| Package 1 Length | 19.700 cm |
| Package 1 Weight | 3.320 kg |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 30.000 cm |
| Package 2 Width | 40.000 cm |
| Package 2 Length | 60.000 cm |
| Package 2 Weight | 20.800 kg |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 24 |
| Package 3 Height | 45.000 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 120.000 cm |
| Package 3 Weight | 95.200 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free | Yes |