

# Product data sheet

## Characteristics

# LV480828

## Handle with electronic fuse monitor, FuPacT ISFT630



### Main

Product or component type	Fuse monitor
Electrical circuit type	Electronic
Device application	Signalling
Accessory / separate part category	Electrical accessory

### Complementary

Range compatibility	FuPacT FuPacT ISFT ISFT630 fuse-switch disconnector
Control type	Handle
[Ue] rated operational voltage	400...690 V AC 50/60 Hz
[Ie] rated operational current	5 A (AC-15) at 200...240 V AC 5 A (AC-15) at 250 V AC 5 A (DC-13) at 24 V DC
Rated breaking capacity	2 kA
Power consumption in VA	3 VA
[Ith] conventional free air thermal current	5 A
[Ui] rated insulation voltage	250 V
Minimum load	10 mA 24 V
Standards	EN 61000-4-4 EN 55022 ENV 50204 EN 61000-4-6 EN 61000-4-3 EN 61000-4-2 EN 61000-4-5
Product certifications	CE
Net weight	0.2 kg

### Environment

IP degree of protection	IP20
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...70 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.0 cm
Package 1 Width	27.5 cm
Package 1 Length	33.0 cm
Package 1 Weight	1.089 kg
Unit Type of Package 2	S04
Number of Units in Package 2	3

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	3.9 kg

## Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 Yes