
LVS03010

Rail, PrismaSeT G, for modular device, W300mm





Main

IVIAIII	
Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Rail
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT G duct
Type of rail	Modular
Installed device	Acti 9: fixed C120 without earth leakage protection - control: toggle TeSys: fixed GV2LE TeSys: fixed GV2ME TeSys: fixed GV2RTn Acti 9: fixed iC120 without earth leakage protection - control: toggle ComPact: fixed INS100 - control: direct front rotary handle - vertical installation ComPact: fixed INS160 - control: direct front rotary handle - vertical installation ComPact: fixed INS40 - control: direct front rotary handle - vertical installation ComPact: fixed INS63 - control: direct front rotary handle - vertical installation Acti 9: fixed modular device Multi9: fixed modular device Multi9: fixed NG125 without earth leakage protection - control: toggle Multi9: fixed NG125 NA - control: toggle Acti 9: fixed C120 with earth leakage protection - control: toggle Acti 9: fixed iC120 with earth leakage protection - control: toggle Multi9: fixed NG125 with earth leakage protection - control: toggle ComPact: fixed INS125 - control: direct front rotary handle - vertical installation Acti 9: fixed modular device <= 40 A Multi9: fixed modular device <= 40 A Multi9: fixed modular device <= 40 A
Poles description	1 x 3P: fixed C120 1 x 4P: fixed C120 1 x 3P: fixed iC120 1 x 4P: fixed iC120 1 x 3P: fixed iC120 1 x 3P: fixed INS100 vertical installation 1 x 4P: fixed INS100 vertical installation 1 x 3P: fixed INS160 vertical installation 1 x 4P: fixed INS160 vertical installation 1 x 3P: fixed INS40 vertical installation 1 x 3P: fixed INS40 vertical installation 1 x 3P: fixed INS63 vertical installation 1 x 3P: fixed NG125 1 x 4P: fixed NG125 1 x 3P: fixed NG125 NA 1 x 4P: fixed INS125 vertical installation 1 x 4P: fixed INS125 vertical installation 1 x 4P: fixed INS125 vertical installation 4 x 3P: fixed GV2LE 4 x 3P: fixed GV2ME 4 x 3P: fixed GV2RTn

Complementary

Installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
Number of vertical modules [50 mm]	· ·
	mounted duct 4 module(s): NG125 with earth leakage protection, direct in 300 mm Widefloor- standing duct 4 module(s): NG125 with earth leakage protection, direct in 300 mm Widewall- mounted duct
9 mm pitches	20
Quantity per set	Set of 1
leight	52 mm
Vidth	218 mm
epth	100 mm
let weight	0.14 kg
Colour	Natural
Material	Metal
Environment	
Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.2 cm
Package 1 Width	10.5 cm
Package 1 Length	21.8 cm
Package 1 Weight	169.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	13.6 cm
Package 2 Width	21.2 cm
Package 2 Length	25.4 cm
Package 2 Weight	1.861 kg
Unit Type of Package 3	P12
Number of Units in Package 3	300
Package 3 Height	40.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	66.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product