LVS03293

Front plate, PrismaSeT P and G, for Vigi NSX 100/250, 11M, vertical, toggle, W300, white, RAL 9003





Main Range PrismaSeT Range of product PrismaSeT G PrismaSeT P Product or component Front plate Accessory / separate Installation accessory part category Range compatibility PrismaSeT PrismaSeT G duct PrismaSeT PrismaSeT P cubicle PrismaSeT PrismaSeT Pack 250 duct Type of front plate Cut-out Installed device ComPact: fixed NSX100...160 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX100...160 with earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX250 with earth leakage protection - control: toggle - vertical installation 1 x 4P: mounting plate support: NSX100...160 Poles description vertical installation 1 x 4P: mounting plate support: NSX250 vertical installation 1 x 3P: mounting plate support: NSX100...160 vertical installation 1 x 3P: mounting plate support: NSX250 vertical

installation Vertical

Complementary

Enclosure/cubicle description	Floor-standing duct - width 300 mm
	Wall-mounted duct - width 300 mm
	Cubicle duct - width 400 mm depth 400 mm
	Pack enclosure - width 300 mm
Connection position	Front connection
	Direct connection
Number of vertical modules [50 mm]	11
Standards	IEC 61439-2
	IEC 61439-1
Product certifications	ASTA
Material	Steel
Surface finish	Textured
	Matt
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	550 mm
Width	300 mm
Net weight	1.16 kg

Operating position

r technical characteristics of the performance of the products contained herein. mining suitability or reliability of these products for specific user applications. risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof the responsible or liable for misuse of the information contained herein. The information provided in this documentation contains general descriptions and/or this documentation is not intended as a substitute for and is not to be used for detem It is the duty of any such user or integrator to perform the appropriate and complete in It is the duty of any such user or integrator to perform the appropriate and complete in It is the duty of any such users of substitutes SAS nor any of its affiliates or subsidiaries shall

Quantity per set	Set of 1
Functional unit	300 mm PrismaSeT G floor-standing duct ComPact NSX100160 with fixed toggle vertical 4P 1 direct 11
	300 mm PrismaSeT G wall-mounted duct ComPact NSX100160 with fixed toggle vertical 4P 1 direct 11
	400 mm 400 mm PrismaSeT P cubicle ComPact NSX100160 with fixed toggle
	vertical 3P 1 front connection 11
	400 mm 400 mm PrismaSeT P cubicle ComPact NSX100160 with fixed toggle vertical 4P 1 front connection 11
	400 mm 400 mm PrismaSeT P cubicle ComPact NSX100160 with plug-in toggle vertical 3P 1 front connection 11
	400 mm 400 mm PrismaSeT P cubicle ComPact NSX100160 with plug-in
	toggle vertical 4P 1 front connection 11
	300 mm PrismaSeT G floor-standing duct ComPact NSX250 with fixed toggle vertical 4P 1 direct 11
	300 mm PrismaSeT G wall-mounted duct ComPact NSX250 with fixed toggle vertical 4P 1 direct 11
	400 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed toggle vertical 3P 1 front connection 11
	400 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed toggle vertical 4P 1 front connection 11
	400 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with plug-in toggle
	vertical 3P 1 front connection 11 400 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with plug-in toggle
	vertical 4P 1 front connection 11
	300 mm PrismaSeT G floor-standing duct ComPact NSX100160 with fixed
	toggle vertical 3P 1 direct with long terminal shield 13
	300 mm PrismaSeT G wall-mounted duct ComPact NSX100160 with fixed
	toggle vertical 3P 1 direct with long terminal shield 13 300 mm PrismaSeT G floor-standing duct ComPact NSX100160 with fixed
	toggle vertical 4P 1 direct with long terminal shield 13
	300 mm PrismaSeT G wall-mounted duct ComPact NSX100160 with fixed
	toggle vertical 4P 1 direct with long terminal shield 13
	300 mm Prisma Pack 250 Pack enclosure ComPact NSX100160 with fixed
	toggle vertical 3P 1 direct with long terminal shield 13 300 mm Prisma Pack 250 Pack enclosure ComPact NSX100160 with fixed
	toggle vertical 4P 1 direct with long terminal shield 13
	300 mm PrismaSeT G floor-standing duct ComPact NSX250 with fixed toggle
	vertical 3P 1 direct with long terminal shield 13
	300 mm PrismaSeT G wall-mounted duct ComPact NSX250 with fixed toggle
	vertical 3P 1 direct with long terminal shield 13
	300 mm PrismaSeT G floor-standing duct ComPact NSX250 with fixed toggle vertical 4P 1 direct with long terminal shield 13
	300 mm PrismaSeT G wall-mounted duct ComPact NSX250 with fixed toggle
	vertical 4P 1 direct with long terminal shield 13
	300 mm Prisma Pack 250 Pack enclosure ComPact NSX250 with fixed toggle
	vertical 3P 1 direct with long terminal shield 13
	300 mm Prisma Pack 250 Pack enclosure ComPact NSX250 with fixed toggle vertical 4P 1 direct with long terminal shield 13

Packing Units

3 - 3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	26.5 cm
Package 1 Length	56.5 cm
Package 1 Weight	1.16 kg
Unit Type of Package 2	S04
Number of Units in Package 2	12
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	16.644 kg
Unit Type of Package 3	P12
Number of Units in Package 3	48
Package 3 Height	43.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	76.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product