LVS03332

Front plate, PrismaSeT G, for NSXm/VIGI/SDx, 3M, horizontal, fixed, toggle, cut-out, W850





| Main | |
|------------------------------------|---------------------------------|
| Range | PrismaSeT |
| Range of product | PrismaSeT G |
| Product or component type | Front plate |
| Accessory / separate part category | Installation accessory |
| Range compatibility | PrismaSeT PrismaSeT G enclosure |

Type of front plate

Cut-out

ComPact: fixed NSXm without earth leakage protection - control: toggle - horizontal installation ComPact: fixed NSXm with earth leakage protection - control: toggle - horizontal installation

Poles description 1 x 3P or 4P: mounting plate support: NSXm horizontal installation

Operating position Horizontal

Complementary

| Enclosure/cubicle description | Floor-standing enclosure - width 850 mm |
|------------------------------------|--|
| Connection position | Direct connection |
| Number of vertical modules [50 mm] | 3 |
| Standards | IEC 61439-1 IEC 61439-2 |
| Product certifications | ASTA |
| Surface finish | Textured Matt |
| Protective treatment | Electrophoresis treatment and hot-polymerised polyester epoxy powder |
| Colour | White (RAL 9003) |
| Height | 150 mm |
| Quantity per set | Set of 1 |
| Functional unit | 850 mm PrismaSeT G floor-standing enclosure ComPact NSXm without fixed toggle horizontal 3P or 4P 1 direct 3 850 mm PrismaSeT G floor-standing enclosure ComPact NSXm with fixed toggle horizontal 3P or 4P 1 direct 3 |

Packing Units

| i acking chits | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3 cm |
| Package 1 Width | 15 cm |
| Package 1 Length | 75 cm |
| Package 1 Weight | 1.121 kg |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 5 |
| Package 2 Height | 16.5 cm |
| Package 2 Width | 53.5 cm |
| Package 2 Length | 82 cm |
| Package 2 Weight | 6.548 kg |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 15 |
| | |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| Package 3 Height | 45 cm |
|------------------|---------|
| Package 3 Width | 80 cm |
| Package 3 Length | 120 cm |
| Package 3 Weight | 31.5 kg |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|-----------------------------|--|
| REACh Regulation | [™] REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | ₫Yes |
| Circularity Profile | No need of specific recycling operations |
| PVC free | Yes |
| Halogen content performance | Halogen free plastic parts product |