

Product data sheet

Characteristics

LVS03352

Front plate, PrismaSeT P and G, transparent,
for enclosure W300, 4M, white, RAL 9003



Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G duct PrismaSeT PrismaSeT P duct
Type of front plate	Transparent
Installed device	TeSys: fixed TeSys U - horizontal installation TeSys: fixed GV2 + D or K contactors <= 40 A - horizontal installation
Poles description	4 x 3P: modular rail support: GV2 + D or K contactors <= 40 A horizontal installation 4 x 3P: modular rail support: TeSys U horizontal installation
Operating position	Horizontal

Complementary

Enclosure/cubicle description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle duct - width 400 mm depth 400 mm
Connection position	Direct connection
Number of vertical modules [50 mm]	4
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASTA
Material	Glass
Surface finish	Textured Matt
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	200 mm
Width	300 mm
Net weight	0.54 kg
Quantity per set	Set of 1
Functional unit	300 mm PrismaSeT G floor-standing duct TeSys GV2 + D or K contactors <= 40 A fixed horizontal 3P 4 direct 5 300 mm PrismaSeT G wall-mounted duct TeSys GV2 + D or K contactors <= 40 A fixed horizontal 3P 4 direct 5 400 mm 400 mm PrismaSeT P cubicle 300 mm PrismaSeT G floor-standing duct TeSys TeSys U fixed horizontal 3P 4 direct 5 300 mm PrismaSeT G wall-mounted duct TeSys TeSys U fixed horizontal 3P 4 direct 5 300 mm PrismaSeT G floor-standing duct TeSys TeSys U fixed horizontal 3P 4 direct 4 300 mm PrismaSeT G wall-mounted duct TeSys TeSys U fixed horizontal 3P 4 direct 4

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	21.5 cm
Package 1 Length	26.5 cm
Package 1 Weight	613.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.538 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product