





Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Rail
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT P
Type of rail	Modular
Installed device	Acti 9: fixed C120 without earth leakage protection - control: toggle TeSys: fixed GV2LE TeSys: fixed GV2ME TeSys: fixed GV2RTn Acti 9: fixed iC120 without earth leakage protection - control: toggle Vigilohm: IM20 Vigilohm: IM20H ComPact: fixed INS100 - control: direct front rotary handle - vertical installation ComPact: fixed INS160 - control: direct front rotary handle - vertical installation ComPact: fixed INS40 - control: direct front rotary handle - vertical installation ComPact: fixed INS63 - control: direct front rotary handle - vertical installation Acti 9: fixed modular device Multi9: fixed modular device Multi9: fixed NG125 without earth leakage protection - control: toggle Multi9: fixed NG125 NA - control: toggle Vigirex: RH10 Vigirex: RH21 Vigirex: RH99 Acti 9: fixed C120 with earth leakage protection - control: toggle Acti 9: fixed iC120 with earth leakage protection - control: toggle Multi9: fixed NG125 with earth leakage protection - control: toggle Acti 9: fixed 1/2 or 1 module lamp - horizontal installation ComPact: fixed INS125 - control: direct front rotary handle - vertical installation Acti 9: fixed modular device <= 40 A Multi9: fixed modular device <= 40 A Vigilohm: IM10 Vigilohm: IM10H Vigilohm: IM9 Vigilohm: IM9-OL Acti 9: measurement device Multi9: measurement device Vigirex: RH197M
Poles description	1 x 3P: fixed C120 1 x 4P: fixed C120 9 x 3P: fixed GV2LE 9 x 3P: fixed GV2ME 9 x 3P: fixed GV2RTn 1 x 3P: fixed iC120 1 x 4P: fixed iC120 1 x 3P: fixed INS100 vertical installation 1 x 4P: fixed INS100 vertical installation 1 x 3P: fixed INS160 vertical installation 1 x 4P: fixed INS160 vertical installation 1 x 3P: fixed INS40 vertical installation 1 x 4P: fixed INS40 vertical installation 1 x 3P: fixed INS63 vertical installation 1 x 4P: fixed INS63 vertical installation 1 x 3P: fixed NG125 1 x 4P: fixed NG125 1 x 3P: fixed NG125 NA 1 x 4P: fixed NG125 NA 1 x 3P: fixed INS125 vertical installation 1 x 4P: fixed INS125 vertical installation

Complementary

Installation description	Cubicle - width 650 mm depth 400 mm
Enclosure nominal height	2000 mm
Number of vertical modules [50 mm]	2 module(s): 1/2 or 1 module lamp, direct in 650 mm Widecubicle 5 module(s): C120 without earth leakage protection , direct in 650 mm Widecubicle 3 module(s): GV2LE, direct in 650 mm Widecubicle 3 module(s): GV2ME, direct in 650 mm Widecubicle 3 module(s): GV2RTn, direct in 650 mm Widecubicle 5 module(s): iC120 without earth leakage protection , direct in 650 mm Widecubicle 4 module(s): IM10 in 650 mm Widecubicle 4 module(s): IM10H in 650 mm Widecubicle 4 module(s): IM20 in 650 mm Widecubicle 4 module(s): IM20H in 650 mm Widecubicle 3 module(s): IM9 in 650 mm Widecubicle 3 module(s): IM9-OL in 650 mm Widecubicle 4 module(s): INS100, direct in 650 mm Widecubicle 5 module(s): INS100, direct in 650 mm Widecubicle 4 module(s): INS125, direct in 650 mm Widecubicle 5 module(s): INS125, direct in 650 mm Widecubicle 4 module(s): INS160, direct in 650 mm Widecubicle 5 module(s): INS160, direct in 650 mm Widecubicle 4 module(s): INS40, direct in 650 mm Widecubicle 4 module(s): INS63, direct in 650 mm Widecubicle 3 module(s): measurement device in 650 mm Widecubicle 3 module(s): modular device <= 40 A, direct in 650 mm Widecubicle 8 module(s): modular device <= 40 A, direct in 650 mm Widecubicle 4 module(s): modular device, direct in 650 mm Widecubicle 5 module(s): NG125 without earth leakage protection , direct in 650 mm Widecubicle 5 module(s): NG125 NA, direct in 650 mm Widecubicle 3 module(s): RH10 in 650 mm Widecubicle 3 module(s): RH197M in 650 mm Widecubicle 3 module(s): RH21 in 650 mm Widecubicle 3 module(s): RH99 in 650 mm Widecubicle 5 module(s): C120 with earth leakage protection , direct in 650 mm Widecubicle 5 module(s): iC120 with earth leakage protection , direct in 650 mm Widecubicle 5 module(s): NG125 with earth leakage protection , direct in 650 mm Widecubicle
9 mm pitches	48
Quantity per set	Set of 1
Height	43 mm
Width	592 mm
Depth	126 mm
Net weight	0.5 kg
Colour	Natural
Material	Metal

Environment

Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASTA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.300 cm
Package 1 Width	12.800 cm
Package 1 Length	60.500 cm
Package 1 Weight	499.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	14.800 cm
Package 2 Width	27.600 cm
Package 2 Length	62.700 cm

Package 2 Weight	6.269 kg
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	67.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	137.380 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product