


LVS03422

Mounting plate, PrismaSeT P, for NSX/NSX
Vigi250/NS250 3P/4P, vertical fixed, rot handle,
mot mech





Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT P cubicle
Installation description	Cubicle - width 650 mm depth 400 mm
Installed device	EasyPact: fixed CVS100...160 without earth leakage protection - control: direct front rotary handle - vertical installation EasyPact: fixed CVS250 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation EasyPact: fixed CVS100...160 with earth leakage protection - control: direct front rotary handle - vertical installation EasyPact: fixed CVS250 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX100...160 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX100...160 without earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX100...160 with earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: motor mechanism - vertical installation
Poles description	4 x 3P: fixed CVS100...160 vertical installation 3 x 4P: fixed CVS100...160 vertical installation 4 x 3P: fixed CVS250 vertical installation 3 x 4P: fixed CVS250 vertical installation 4 x 3P: fixed NSX100...160 vertical installation 3 x 4P: fixed NSX100...160 vertical installation 4 x 3P: fixed NSX250 vertical installation 3 x 4P: fixed NSX250 vertical installation

Number of vertical modules [50 mm]	9 module(s): CVS100...160 without earth leakage protection , direct in 650 mm Widecubicle 9 module(s): CVS250 without earth leakage protection , direct in 650 mm Widecubicle 6 module(s): NSX100...160 without earth leakage protection , Linergy FC in 650 mm Widecubicle 8 module(s): NSX100...160 without earth leakage protection , direct in 650 mm Widecubicle 7 module(s): NSX250 without earth leakage protection , Linergy FC in 650 mm Widecubicle 9 module(s): NSX250 without earth leakage protection , direct in 650 mm Widecubicle 11 module(s): CVS100...160 with earth leakage protection , direct in 650 mm Widecubicle 11 module(s): CVS250 with earth leakage protection , direct in 650 mm Widecubicle 8 module(s): NSX100...160 with earth leakage protection , Linergy FC in 650 mm Widecubicle 10 module(s): NSX100...160 with earth leakage protection , direct in 650 mm Widecubicle 9 module(s): NSX250 with earth leakage protection , Linergy FC in 650 mm Widecubicle 11 module(s): NSX250 with earth leakage protection , direct in 650 mm Widecubicle
Standards	IEC 61439-2
Product certifications	ASTA

Complementary

Material	Sheet steel
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Matt Textured
Colour	White (RAL 9003)
Width	606 mm
Height	147 mm
Depth	372 mm

Net weight	2.28 kg
Functional unit	650 mm 400 mm PrismaSeT P cubicle EasyPact CVS100...160 without fixed direct front rotary handle vertical 3P 4 direct 9 162.5 mm 650 mm 400 mm PrismaSeT P cubicle EasyPact CVS100...160 without fixed direct front rotary handle vertical 4P 3 direct 9 162.5 mm 650 mm 400 mm PrismaSeT P cubicle EasyPact CVS250 without fixed direct front rotary handle vertical 3P 4 direct 9 162.5 mm 650 mm 400 mm PrismaSeT P cubicle EasyPact CVS250 without fixed direct front rotary handle vertical 4P 3 direct 9 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed direct front rotary handle vertical 3P 4 Linergy FC 6 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed motor mechanism vertical 3P 4 Linergy FC 6 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed direct front rotary handle vertical 4P 3 Linergy FC 6 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed motor mechanism vertical 4P 3 Linergy FC 6 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed direct front rotary handle vertical 3P 4 direct 8 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed direct front rotary handle vertical 4P 3 direct 8 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed motor mechanism vertical 3P 4 direct 8 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed motor mechanism vertical 4P 3 direct 8 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 Linergy FC 7 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed motor mechanism vertical 3P 4 Linergy FC 7 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 Linergy FC 7 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed motor mechanism vertical 4P 3 Linergy FC 7 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 direct 9 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 direct 9 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed motor mechanism vertical 3P 4 direct 9 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed motor mechanism vertical 4P 3 direct 9 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 with fixed motor mechanism vertical 4P 3 Linergy FC 8 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 with fixed direct front rotary handle vertical 3P 4 direct 10 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 with fixed direct front rotary handle vertical 4P 3 direct 10 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 with fixed motor mechanism vertical 3P 4 direct 10 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 with fixed motor mechanism vertical 4P 3 direct 10 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed direct front rotary handle vertical 3P 4 Linergy FC 9 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed motor mechanism vertical 3P 4 Linergy FC 9 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed direct front rotary handle vertical 4P 3 Linergy FC 9 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed motor mechanism vertical 4P 3 Linergy FC 9 62.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed direct front rotary handle vertical 3P 4 direct 11 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed direct front rotary handle vertical 4P 3 direct 11 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed motor mechanism vertical 3P 4 direct 11 162.5 mm 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed motor mechanism vertical 4P 3 direct 11 162.5 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.500 cm
Package 1 Width	14.600 cm
Package 1 Length	58.000 cm
Package 1 Weight	2.397 kg
Unit Type of Package 2	S04

Number of Units in Package 2	6
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	15.140 kg
Unit Type of Package 3	P12
Number of Units in Package 3	72
Package 3 Height	102.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	195.500 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product