
LVS03716

Front plate, PrismaSeT P, for ComPacT NS1600b to 3200, 8M, fixed, white, RAL 9003





Main	
Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT P cubicle
Type of front plate	Cut-out
Installed device	ComPact: fixed NS1600b - control: toggle - vertical installation ComPact: fixed NS20003200 - control: toggle - vertical installation
Poles description	1 x 3P: mounting plate support: NS1600b vertical installation 1 x 4P: mounting plate support: NS1600b vertical installation 1 x 3P: mounting plate support: NS20003200 vertical installation 1 x 4P: mounting plate support: NS20003200 vertical installation
Operating position	Horizontal

Complementary

Complementary	
Enclosure/cubicle description	Cubicle - width 650 mm depth 400 mm Cubicle - width 650 mm depth 600 mm
Connection position	Front connection
Number of vertical modules [50 mm]	8
Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA
Material	Steel
Surface finish	Textured Matt
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	400 mm
Width	500 mm
Net weight	1.02 kg
Quantity per set	Set of 1
Functional unit	650 mm 400 mm PrismaSeT P cubicle ComPact NS1600b fixed toggle vertical 3P 1 front connection on adaptor 14 650 mm 400 mm PrismaSeT P cubicle ComPact NS1600b fixed toggle vertical 4P 1 front connection on adaptor 14 650 mm 600 mm PrismaSeT P cubicle ComPact NS20003200 fixed toggle vertical 3P 1 front connection on adaptor 16 650 mm 600 mm PrismaSeT P cubicle ComPact NS20003200 fixed toggle vertical 4P 1 front connection on adaptor 16

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent or and is not to be used for determining suitability or inhability of these products for specific user applications. It is the dourn aren in integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2 cm
Package 1 Width	41 cm
Package 1 Length	51 cm
Package 1 Weight	1.216 kg
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	11.5 cm
Package 2 Width	43 cm
Package 2 Length	53 cm
Package 2 Weight	7.8 kg
Unit Type of Package 3	P12
Number of Units in Package 3	48
Package 3 Height	56.5 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	73 kg

Offer Sustainability

<u></u>	
Sustainable offer status	Green Premium product
REACh Regulation	☐ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product