



Main

Range	Linergy
Range of product	Linergy
Product or component type	Flexible connection
Product name	Linergy DX
Product name	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure PrismaSeT PrismaSeT Pack 250 enclosure Linergy Linergy DX distribution block
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2, inside enclosure IEC 61439-1, inside enclosure
Product certifications	ASTA

Complementary

Cubicle-device connection	Linergy DX distribution block
Installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 800 mm Pack enclosure - width 555 mm Pack enclosure - width 600 mm
Installed device	Multi9: fixed NG125 without earth leakage protection - control: toggle Multi9: fixed NG125 with earth leakage protection - control: toggle ComPact: fixed INS40 - control: direct front rotary handle vertical installation ComPact: fixed INS63 - control: direct front rotary handle vertical installation ComPact: fixed INS100 - control: direct front rotary handle vertical installation ComPact: fixed INS125 - control: direct front rotary handle vertical installation ComPact: fixed INS160 - control: direct front rotary handle vertical installation Acti 9: fixed iC120 with earth leakage protection - control: toggle Acti 9: fixed iC120 without earth leakage protection - control: toggle Multi9: fixed NG125 NA - control: toggle ComPact: fixed NG160 NA without earth leakage protection - control: toggle Acti 9: fixed C120 with earth leakage protection - control: toggle Acti 9: fixed C120 without earth leakage protection - control: toggle ComPact: fixed NG160 with earth leakage protection - control: toggle ComPact: fixed NG160 without earth leakage protection - control: toggle ComPact: fixed NSXm without earth leakage protection - control: toggle vertical installation ComPact: fixed NSXm with earth leakage protection - control: toggle vertical installation
Condition of use	Additional connector needed for INS40...160 (to be ordered separately)
[I _e] rated operational current	125 A
Length	240 mm
Net weight	0.52 kg

Quantity per set	Set of 4
------------------	----------

Life Is On | Schneider
rotary hand

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.2 cm
Package 1 Width	4.5 cm
Package 1 Length	36.5 cm
Package 1 Weight	535.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	8.249 kg
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	42.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	143.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes