



Main

Range	Lineryg
Range of product	Lineryg
Product or component type	Connection
Product name	Lineryg BW
Product name	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure Lineryg Lineryg BW busbar
Standards	IEC 61439-1, inside enclosure IEC 61439-2, inside enclosure
Product certifications	ASTA

Complementary

Cubicle-device connection	Lineryg BS busbar Lineryg FH comb busbar
Poles description	4P
Installation description	Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing enclosure - width 850 mm Pack enclosure - width 550 mm
Installed device	Multi9: NG125 ComPact: INS125
[I _e] rated operational current	125 A
Material	Copper Plastic
Colour	Copper Black (RAL 9005)
Length	230 mm
Net weight	0.42 kg
Quantity per set	Set of 4

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.000 cm
Package 1 Width	5.000 cm
Package 1 Length	24.000 cm
Package 1 Weight	431.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.578 kg
Unit Type of Package 3	P12
Number of Units in Package 3	80

Package 3 Height	28.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	49.000 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free plastic parts product