
LVS04151

Tap-off unit, Linergy BW, 55A, spring terminals 1 x 6mm² + 1 x 10mm², IPXXB, set of 12





Main	
Range	Linergy
Range of product	Linergy BW
Product or component type	Tap-off unit
Accessory / separate part category	Connection accessory
Range compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure Linergy Linergy BW busbar
Product destination	Busbar

Complementary

Installation description	Cubicle	
	Floor-standing enclosure	
	Wall-mounted enclosure	
	Pack enclosure	
[le] rated operational current	55 A	
Connections - terminals	1 spring terminal 6 mm ²	
	1 spring terminal 10 mm²	
Quantity per set	Set of 12	
Net weight	0.36 kg	

IPxx B

Environment

IP degree of protection

Packing Units		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.8 cm	
Package 1 Width	5.0 cm	
Package 1 Length	23.0 cm	
Package 1 Weight	357.0 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	
Package 2 Height	7.5 cm	
Package 2 Width	23.0 cm	
Package 2 Length	25.5 cm	
Package 2 Weight	3.581 kg	
Unit Type of Package 3	P06	
Number of Units in Package 3	600	
Package 3 Height	88.0 cm	
Package 3 Width	60.0 cm	
Package 3 Length	80.0 cm	

Package 3 Weight

221.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product