



Main

Range	Linergy
Range of product	Linergy
Product or component type	Busbar
Product name	Linergy BS
Range compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure
Busbar description	Flat bar
Quantity per set	Set of 4

Complementary

Installation direction	Vertical, operating position: rear
Installation description	Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
[Ie] rated operational current	400 A at 35 °C
[Icw] rated short-time withstand current	20 kA (1 s) for 4 supports
[Ipk] rated peak withstand current	55 kA
Busbar cross section	32 x 5 mm
Length	1400 mm
Width	32 mm
Depth	5 mm
Net weight	8 kg
Colour	Natural
Type of busbar connection	M6 threaded hole
Connection pitch	Connection each 25 mm

Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.600 cm
Package 1 Width	17.000 cm
Package 1 Length	154.000 cm
Package 1 Weight	8.000 kg
Unit Type of Package 2	P2M
Number of Units in Package 2	56
Package 2 Height	29.000 cm
Package 2 Width	120.000 cm

Package 2 Length	200.000 cm
Package 2 Weight	461.500 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations  Circularity Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product