
LVS04191

Busbar support, PrismaSeT P and G, for Linergy BS rear busbar, 25kA, 400A





Main	
Range	Linergy
Range of product	Linergy
Product or component type	Busbar support
Product name	Linergy BS
Range compatibility	Linergy Linergy BS busbar PrismaSeT PrismaSeT P enclosure

PrismaSeT PrismaSeT G enclosure

Com	plemen	tarv

Cubicle-device connection	Linergy BS rear busbar	
Installation description	Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing enclosure - width 850 mm Extension enclosure - width 600 mm	
Permissible current	160 A - busbar cross section: 15 x 5 mm 250 A - busbar cross section: 20 x 5 mm 400 A - busbar cross section: 32 x 5 mm	
[lcw] rated short-time withstand current	10 KA (1 s) at 160 A for 450 mm between support centres 15 KA (1 s) at 250 A for 450 mm between support centres 20 KA (1 s) at 400 A for 300 mm between support centres 25 kA (1 s) at 400 A for 225 mm between support centres	
Quantity per set	Set of 1	
Net weight	0.24 kg	

Environment

Littiioiiiioiit		
Standards	IEC 61439-2 IEC 61439-1	
Product certifications	ASTA	

Packing Units

r doming of the	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	5.300 cm
Package 1 Length	46.300 cm
Package 1 Weight	251.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	6.000 cm
Package 2 Width	51.200 cm
Package 2 Length	52.000 cm
Package 2 Weight	2.746 kg
Unit Type of Package 3	P12
Number of Units in Package 3	280

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intelability of these products for specific user applications. It is the douty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 3 Height	71.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	89.500 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	[™] Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes