
## LVS04424

connection, Linergy LGY, for NSX250, 4P, 250A, horizontal plug-in with toggle





Main	
Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Connection
Product name	PrismaSeT PrismaSeT P enclosure
Accessory / separate part category	Connection accessory
Standards	IEC 61439-2, inside enclosure IEC 61439-1, inside enclosure
Product certifications	ASTA

## Complementary

Cubicle-device connection	Linergy busbar
Poles description	4P
Installation description	Cubicle - width 650 mm
Installed device	ComPact: fixed NSX100160 with earth leakage protection - control: toggle horizontal installation ComPact: fixed NSX250 with earth leakage protection - control: toggle horizontal installation ComPact: fixed NSX100160 without earth leakage protection - control: toggle horizontal installation ComPact: fixed NSX250 without earth leakage protection - control: toggle horizontal installation
[le] rated operational current	250 A
Busbar cross section	20 x 3 mm
Net weight	1.28 kg
Quantity per set	Set of 1
Functional unit	650 mm 400 mm PrismaSeT P cubicle ComPact NSX100160 without fixed toggle horizontal 4P 1 direct 4 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed toggle horizontal 4P 1 direct 4 650 mm 400 mm PrismaSeT P cubicle ComPact NSX100160 with fixed toggle horizontal 4P 1 direct 4 650 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed toggle horizontal 4P 1 direct 4

## **Packing Units**

1 doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	27.5 cm
Package 1 Length	30.0 cm
Package 1 Weight	1.218 kg
Unit Type of Package 2	P12
Number of Units in Package 2	60
Package 2 Height	36.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	84.5 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Circularity Profile	No need of specific recycling operations