


Product data sheet

Characteristics

LVS04502

Profile busbar, Linergy LGYE, 630A, for a vertical installation, 32.5x42.5mm, L1670mm



Main

Range	Linergy
Range of product	Linergy
Product or component type	Profile busbar
Product name	Linergy LGY
Range compatibility	PrismaSeT PrismaSeT P enclosure
Busbar description	Linergy
Quantity per set	Set of 1

Complementary

Installation direction	Vertical, operating position: rear Vertical, operating position: lateral
Installation description	Cubicle - width 650 mm Cubicle - width 650 + 150 mm
[Ui] rated insulation voltage	1000 V
[Uiimp] rated impulse withstand voltage	12 kV (degree of pollution: 3)
[Ie] rated operational current	630 A
[Icw] rated short-time withstand current	25 kA (1 s) for 3 supports (rear position) 25 kA (1 s) for 3 supports (lateral position)
Permissible current	680 A at 35 °C: <= IP31 590 A at 35 °C: > IP31
Busbar cross section	32.5 x 42.5 mm
Length	1670 mm
Net weight	1.56 kg
Colour	Natural
Type of busbar connection	Single t-slot
Connection pitch	Free connection position

Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.750 cm
Package 1 Width	4.750 cm
Package 1 Length	177.000 cm
Package 1 Weight	1.418 kg
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Height	7.500 cm
Package 2 Width	9.500 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 2 Length	177.000 cm
Package 2 Weight	5.673 kg
Unit Type of Package 3	P2M
Number of Units in Package 3	80
Package 3 Height	29.000 cm
Package 3 Width	120.000 cm
Package 3 Length	200.000 cm
Package 3 Weight	136.000 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product