LVS04510

Profile busbar, Linergy LGYE, 4000A, for a vertical installation, L1625mm





Main

| Range | Linergy |
|---------------------------|---------------------------------|
| Range of product | Linergy |
| Product or component type | Profile busbar |
| Product name | Linergy LGYE |
| Range compatibility | PrismaSeT PrismaSeT P enclosure |
| Busbar description | Linergy |
| Quantity per set | Set of 1 |

Complementary

| Installation direction | Vertical, operating position: lateral | |
|--|---|--|
| | Horizontal, operating position: top | |
| | Horizontal, operating position: bottom | |
| Installation description | Cubicle - width 650 mm | |
| | Cubicle - width 650 + 150 mm | |
| | Cubicle duct - width 300 mm | |
| [Ui] rated insulation voltage | 1000 V | |
| [Uimp] rated impulse withstand voltage | 12 kV (degree of pollution: 3) | |
| [le] rated operational current | 4000 A | |
| [lcw] rated short-time withstand current | 60 KA (1 s) for 2 supports (horizontal position) | |
| | 85 KA (1 s) for 3 supports (horizontal position) | |
| | 85 KA (1 s) for 7 supports (lateral position) | |
| | 100 KA (1 s) for 4 supports (horizontal position) | |
| | 100 KA (1 s) for 9 supports (lateral position) | |
| | 60 KA (1 s) for 3 supports (lateral position) | |
| | 75 kA (1 s) for 5 supports (lateral position) | |
| Permissible current | 3620 A at 35 °C: <= IP31 | |
| | 3350 A at 35 °C: > IP31 | |
| Length | 1625 mm | |
| Colour | Natural | |
| Type of busbar connection | Double t-slot | |
| Connection pitch | Free connection position | |

Environment

| Standards | IEC 61439-1 IEC 61439-2 | |
|------------------------|----------------------------|--|
| Product certifications | ASTA | |
| | | |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|-----------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 4.5 cm | |
| Package 1 Width | 15.8 cm | |
| Package 1 Length | 177.5 cm | |
| Package 1 Weight | 18.079 kg | |
| Unit Type of Package 2 | PAL | |

| Number of Units in Package 2 | 18 | |
|------------------------------|----------|--|
| Package 2 Height | 27.0 cm | |
| Package 2 Width | 120.0 cm | |
| Package 2 Length | 202.0 cm | |
| Package 2 Weight | 349.0 kg | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|-----------------------------|--|--|
| REACh Regulation | ☑ REACh Declaration | |
| REACh free of SVHC | Yes | |
| EU RoHS Directive | Compliant EEU RoHS Declaration | |
| Toxic heavy metal free | Yes | |
| Mercury free | Yes | |
| China RoHS Regulation | ☑ China RoHS Declaration | |
| RoHS exemption information | ₫Yes | |
| Environmental Disclosure | Product Environmental Profile | |
| Circularity Profile | No need of specific recycling operations | |
| PVC free | Yes | |
| Halogen content performance | Halogen free plastic parts product | |