



Main

Range	Linergy
Range of product	Linergy
Product or component type	PE conductor flat bar
Product name	Linergy TB
Range compatibility	PrismaSeT PrismaSeT P enclosure
Quantity per set	Set of 1

Complementary

Installation direction	Horizontal Vertical
Installation description	Cubicle
[Ie] rated operational current	400 A
[Icw] rated short-time withstand current	40 kA (1 s) for 3 supports (vertical position) 40 kA (1 s) (horizontal position)
Busbar cross section	25 x 5 mm
Length	1675 mm
Width	25 mm
Depth	5 mm
Net weight	2.06 kg
Colour	Natural
Type of busbar connection	Ø 10 mm drilled hole

Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.500 cm
Package 1 Width	11.500 cm
Package 1 Length	178.000 cm
Package 1 Weight	1.948 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	100
Package 2 Height	32.000 cm
Package 2 Width	120.000 cm
Package 2 Length	202.000 cm
Package 2 Weight	220.000 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product