



### Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Connection
Product name	PrismaSeT PrismaSeT P enclosure
Accessory / separate part category	Interface accessory
Standards	IEC 61439-2, inside enclosure IEC 61439-1, inside enclosure
Product certifications	ASTA

### Complementary

Cubicle-device connection	KT with Canalis
Poles description	4P
Installation description	Cubicle - width 650 mm
Cubicle depth	400 + 400 mm: rear
Installed device	<p>ComPact: drawout NS630b...1000 - control: direct front rotary handle vertical installation</p> <p>ComPact: drawout NS1250 - control: direct front rotary handle vertical installation</p> <p>ComPact: drawout NS630b...1000 - control: motor mechanism vertical installation</p> <p>ComPact: drawout NS1250 - control: motor mechanism vertical installation</p> <p>ComPact: drawout NS630b...1000 - control: toggle vertical installation</p> <p>ComPact: drawout NS1250 - control: toggle vertical installation</p> <p>ComPact: fixed NS630b...1000 - control: toggle vertical installation</p> <p>ComPact: fixed NS1250 - control: toggle vertical installation</p> <p>ComPact: fixed NS630b...1000 - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed NS1250 - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed NS630b...1000 - control: motor mechanism vertical installation</p> <p>ComPact: fixed NS1250 - control: motor mechanism vertical installation</p> <p>ComPact: fixed NS1600 - control: toggle vertical installation</p> <p>ComPact: fixed NS1600 - control: direct front rotary handle vertical installation</p> <p>ComPact: fixed NS1600 - control: motor mechanism vertical installation</p> <p>ComPact: drawout NS1600 - control: direct front rotary handle vertical installation</p> <p>ComPact: drawout NS1600 - control: motor mechanism vertical installation</p> <p>ComPact: drawout NS1600 - control: toggle vertical installation</p> <p>Masterpact: fixed NT06...10 - control: toggle vertical installation</p> <p>Masterpact: fixed NT06...10 - control: motor mechanism vertical installation</p> <p>Masterpact: fixed NT12 - control: toggle vertical installation</p> <p>Masterpact: fixed NT12 - control: motor mechanism vertical installation</p> <p>Masterpact: fixed NT16 - control: toggle vertical installation</p> <p>Masterpact: fixed NT16 - control: motor mechanism vertical installation</p>
[Ie] rated operational current	1600 A
Colour	Natural
Net weight	5.08 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Quantity per set	Set of 1
Functional unit	<p>650 mm 800 mm PrismaSeT P cubicle ComPact NS1250 drawout toggle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS1250 drawout direct front rotary handle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS1250 drawout motor mechanism vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS630b...1000 drawout toggle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS630b...1000 drawout direct front rotary handle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS630b...1000 drawout motor mechanism vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS1250 fixed toggle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS1250 fixed direct front rotary handle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS1250 fixed motor mechanism vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS630b...1000 fixed toggle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS630b...1000 fixed direct front rotary handle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS630b...1000 fixed motor mechanism vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS1600 fixed toggle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS1600 fixed direct front rotary handle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS1600 fixed motor mechanism vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS1600 drawout toggle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS1600 drawout direct front rotary handle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle ComPact NS1600 drawout motor mechanism vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle Masterpact NT06...10 fixed toggle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle Masterpact NT06...10 fixed motor mechanism vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle Masterpact NT12 fixed toggle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle Masterpact NT12 fixed motor mechanism vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle Masterpact NT16 fixed toggle vertical 4P 1 rear connection on Canalis 16</p> <p>650 mm 800 mm PrismaSeT P cubicle Masterpact NT16 fixed motor mechanism vertical 4P 1 rear connection on Canalis 16</p>

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.0 cm
Package 1 Width	15.0 cm
Package 1 Length	19.0 cm
Package 1 Weight	5.185 kg
Unit Type of Package 2	S02
Number of Units in Package 2	2
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	10.649 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product