


# Product data sheet

## Characteristics

# LVS04746

Insulated flexible bar, PrismaSeT P and G, 400 A, busbar size 24 x 5mm, length 1800mm, set of 1



### Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT P
Product or component type	Insulated flexible bar
Product name	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2, inside enclosure IEC 61439-1, inside enclosure
Product certifications	ASTA

### Complementary

Installation description	Cubicle Floor-standing enclosure Wall-mounted enclosure
[Ie] rated operational current	400 A
Busbar cross section	24 x 5 mm
Length	1800 mm
Net weight	2.48 kg
Quantity per set	Set of 1

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.5 cm
Package 1 Width	12.0 cm
Package 1 Length	193.5 cm
Package 1 Weight	2.554 kg
Unit Type of Package 2	P2M
Number of Units in Package 2	100
Package 2 Height	29.5 cm
Package 2 Width	120.0 cm
Package 2 Length	200.0 cm
Package 2 Weight	278.0 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes

---

China RoHS Regulation

China RoHS Declaration

---

RoHS exemption information

Yes

---

Circularity Profile

No need of specific recycling operations

---