
LVS04753

Insulated flexible bar, PrismaSeT P and G, 660 A, busbar size 32 x 8mm, length 1800mm, set of 1





Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT P
Product or component type	Insulated flexible bar
Product name	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure PrismaSeT Prisma iPM L enclosure PrismaSeT Prisma iPM M enclosure
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2, inside enclosure IEC 61439-1, inside enclosure
Product certifications	ASTA

Complementary

Complementary		
Installation description	Cubicle Floor-standing enclosure Wall-mounted enclosure	
Installed device	ComPact: NSX630 ComPact: CVS630	
[le] rated operational current	660 A	
Busbar cross section	32 x 8 mm	
Length	1800 mm	
Net weight	4.88 kg	
Quantity per set	Set of 1	

Packing Units

5	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	11.5 cm
Package 1 Length	194.0 cm
Package 1 Weight	4.827 kg
Unit Type of Package 2	P2M
Number of Units in Package 2	100
Package 2 Height	29.0 cm
Package 2 Width	120.0 cm
Package 2 Length	200.0 cm
Package 2 Weight	501.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations