LVS08122

Door, PrismaSeT G, plain type for enclosure, 6M, W600, IP30, white, RAL 9003





Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Door
Range compatibility	PrismaSeT PrismaSeT G enclosure
Provided equipment	Door Handle Keylock (key 405) Other keylock and insert to be ordered separately 2 hinge
Type of door	Plain
IP degree of protection	IP43 with door, canopy and IP43 gasket IP30 without door IP40 with door IP41 with door and canopy

Complementary

Installation description	Wall-mounted enclosure - width 600 mm Extension enclosure - width 600 mm	
Door opening side	Reversible	
Number of locks	1	
Door opening angle	130 °	
Number of vertical modules [50 mm]	6	
Enclosure material	Handle: polyamide Cover frame: treated sheet steel	
Quantity per set	Set of 1	
Height	330 mm	
Width	600 mm	
Depth	36 mm	
Net weight	2.6 kg	
Surface finish	Textured Matt	
Colour	White (RAL 9003)	

Environment

IK degree of protection	IK08 conforming to EN/IEC 62262
Standards	IEC 61439-2 IEC 61439-1
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	7.000 cm	
Package 1 Width	38.000 cm	
Package 1 Length	64.500 cm	
Package 1 Weight	3.490 kg	
Unit Type of Package 2	P12	
Number of Units in Package 2	24	

Package 2 Height	71.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	95.000 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	[™] China RoHS Declaration
RoHS exemption information	€Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes