LVS08214

Extension enclosure, PrismaSeT G, Floor standing, without side plates, 33M, W600mm, H1880mm, IP30





Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Enclosure extension
Device application	Low voltage electrical distribution
Enclosure type	Functional enclosure delivered in kit form Metal enclosure Indoor enclosure
Enclosure/cubicle description	Floor-standing enclosure - width 600 mm
Kit composition	Uprights Rear plate Top plate Bottom plate plinth
Additional information	Can be combined side by side
Type of front plate	Without to be ordered separately
Number of vertical modules [50 mm]	33
Number of 18 mm modules per row	24
Standards	IEC 61439-1 IEC 61439-2 IEC 62208
Product certifications	ASTA[RETURN]EAC

Complementary

[Ui] rated insulation voltage	1000 V on main rear busbars conforming to IEC 61439-2
Network frequency	50/60 Hz
[In] rated current	630 A at 40 °C conforming to IEC 61439-2
Short-circuit current	50 kA
[lcw] rated short-time withstand current	25 kA 1 s conforming to IEC 61439-1
[lpk] rated peak withstand current	53 kA conforming to IEC 61439-1
Electrical insulation class	Class I
Material	Treated sheet steel
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Textured Matt
Colour	White (RAL 9003)
Width	595 mm
Height	With plinth: 1880 mm
Depth	205 mm
Net weight	24 kg
Quantity per set	Set of 1

Environment

IP degree of protection	IP30 with front plate	
	IP40 with door	
	IP41 with door and canopy	
	IP43 with door, canopy and IP43 gasket	
IK degree of protection	IK07 with front plate	
	IK08 with transparent door	
	IK10 with plain door	
Mechanical robustness	Seismic tests - 2.5G conforming to IEC 60068-2-57	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.000 cm
Package 1 Width	66.000 cm
Package 1 Length	190.000 cm
Package 1 Weight	26.250 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	8
Package 2 Height	95.000 cm
Package 2 Width	120.000 cm
Package 2 Length	202.000 cm
Package 2 Weight	238.000 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	[™] China RoHS Declaration
RoHS exemption information	€Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes