LVS08215

Extension enclosure, PrismaSeT G, Floor standing, without side plates, 36M, W600mm, H2030mm, IP30





Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Enclosure extension
Device application	Low voltage electrical distribution
Enclosure type	Functional enclosure delivered in kit form Metal enclosure Indoor enclosure
Enclosure/cubicle description	Floor-standing enclosure - width 600 mm
Kit composition	Uprights Rear plate Top plate Bottom plate plinth
Additional information	Can be combined side by side
Type of front plate	Without to be ordered separately
Number of vertical modules [50 mm]	36
Number of 18 mm modules per row	24
Standards	IEC 61439-1 IEC 61439-2 IEC 62208
Product certifications	ASTA[RETURN]EAC

Complementary

1000 V on main rear busbars conforming to IEC 61439-2
50/60 Hz
630 A at 40 °C conforming to IEC 61439-2
50 kA
25 kA 1 s conforming to IEC 61439-1
53 kA conforming to IEC 61439-1
Class I
Treated sheet steel
Electrophoresis treatment and hot-polymerised polyester epoxy powder
Textured Matt
White (RAL 9003)
595 mm
With plinth: 2030 mm
205 mm
Set of 1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent or and is not to be used for determining suitability or inhability of these products for specific user applications. It is the dourn aren in integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

IP degree of protection	IP30 with front plate	
	IP40 with door	
	IP41 with door and canopy	
	IP43 with door, canopy and IP43 gasket	
IK degree of protection	IK07 with front plate	
	IK08 with transparent door	
	IK10 with plain door	
Mechanical robustness	Seismic tests - 2.5G conforming to IEC 60068-2-57	

Packing Units

5	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.5 cm
Package 1 Width	66.0 cm
Package 1 Length	189.5 cm
Package 1 Weight	29.5 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	8
Package 2 Height	97.0 cm
Package 2 Width	132.5 cm
Package 2 Length	202.0 cm
Package 2 Weight	256.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes