## Product data sheet Characteristics

# LVS08275

Floor standing duct, PrismaSeT G, W 300mm, H 2030mm (36M), IP30, without side plates





#### Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Duct
Device application	Low voltage electrical distribution
Enclosure type	Functional enclosure delivered in kit form Metal enclosure Indoor enclosure
Enclosure/cubicle description	Floor-standing duct - width 300 mm
Kit composition	Uprights Rear plate Top plate Bottom plate plinth
Additional information	Can be combined side by side
Type of front plate	Without to be ordered separately
Number of vertical modules [50 mm]	36
Number of 18 mm modules per row	10
Standards	IEC 61439-1 IEC 61439-2 IEC 62208
Product certifications	ASTA[RETURN]EAC

#### Complementary

[Ui] rated insulation voltage	1000 V on main rear busbars conforming to IEC 61439-2
Network frequency	50/60 Hz
[In] rated current	630 A at 40 °C conforming to IEC 61439-2
Short-circuit current	50 kA
[lcw] rated short-time withstand current	25 kA 1 s conforming to IEC 61439-1
[lpk] rated peak withstand current	53 kA conforming to IEC 61439-1
Electrical insulation class	Class I
Material	Treated sheet steel
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powde
Surface finish	Textured Matt
Colour	White (RAL 9003)
Width	305 mm
Height	With plinth: 2030 mm
Depth	205 mm
Quantity per set	Set of 1

### Environment

IP degree of protection	IP30 with front plate	
	IP40 with door	
	IP41 with door and canopy	
	IP43 with door, canopy and IP43 gasket	
IK degree of protection	IK07 with front plate	
	IK08 with transparent door	
	IK10 with plain door	
Mechanical robustness	Seismic tests - 2.5G conforming to IEC 60068-2-57	

### Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.000 cm
Package 1 Width	37.500 cm
Package 1 Length	190.000 cm
Package 1 Weight	17.940 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	15
Package 2 Height	83.500 cm
Package 2 Width	120.000 cm
Package 2 Length	202.000 cm
Package 2 Weight	295.000 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	<sup>™</sup> REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes