LVS08326

Door, PrismaSeT G, plain type with frame, 23M, W600, IP55, white, RAL 9003





Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Door
Range compatibility	PrismaSeT PrismaSeT G enclosure
Provided equipment	Door Handle Keylock (key 405) Other keylock and insert to be ordered separately 2 hinge
Type of door	Plain
IP degree of protection	IP55

Complementary

Installation description	Wall-mounted enclosure - width 600 mm Extension enclosure - width 600 mm
Door opening side	Reversible
Number of locks	3
Door opening angle	180 °
Number of vertical modules [50 mm]	23
Enclosure material	Treated sheet steel
Quantity per set	Set of 1
Height	1250 mm
Width	600 mm
Depth	26 mm
Net weight	18.84 kg
Surface finish	Textured Matt
Colour	White (RAL 9003)

Environment

IK degree of protection	IK10 conforming to EN/IEC 62262
Standards	IEC 61439-1 IEC 61439-2
Protective treatment	Electrophoresis treatment and hot-polymerised polyester enoxy powder

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	7.0 cm	
Package 1 Width	60.0 cm	
Package 1 Length	123.0 cm	
Package 1 Weight	18.398 kg	
Unit Type of Package 2	P12	
Number of Units in Package 2	10	
Package 2 Height	86.0 cm	
Package 2 Width	80.0 cm	

Package 2 Length	120.0 cm
Package 2 Weight	196.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Circularity Profile	No need of specific recycling operations