



Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Partial door
Range compatibility	PrismaSeT PrismaSeT G enclosure
Provided equipment	Door 2 hinge 8 mm male triangle insert Insulating plain mounting plate
Type of door	Cut-out
IP degree of protection	IP55

Complementary

Installation description	Wall-mounted enclosure - width 600 mm Floor-standing enclosure - width 600 mm
Number of locks	3
Door opening angle	180 °
Number of vertical modules [50 mm]	4
Additional information	Dimensions of the two holes are 200 x 112 mm
Quantity per set	Set of 1
Height	200 mm
Width	600 mm
Depth	26 mm
Net weight	5.18 kg
Surface finish	Textured Matt
Colour	White (RAL 9003)

Environment

IK degree of protection	IK10 conforming to EN/IEC 62262
Standards	IEC 61439-2 IEC 61439-1
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	24.5 cm
Package 1 Length	59.5 cm
Package 1 Weight	5.18 kg
Unit Type of Package 2	P12
Number of Units in Package 2	6
Package 2 Height	28.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	43.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations