



Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Door
Range compatibility	PrismaSeT PrismaSeT P cubicle duct
Provided equipment	Door Handle Keylock (key 405) Other keylock and insert to be ordered separately 4 hinge Polyurethane joint
Enclosure mounting	Floor-standing
Type of door	Transparent
IP degree of protection	IP55

Complementary

Installation description	Cubicle duct - width 400 mm
Door opening side	Reversible
Number of locks	3
Door opening angle	120 °
Number of vertical modules [50 mm]	36
Enclosure material	Glass Treated sheet steel
Quantity per set	Set of 1
Height	1925 mm
Width	400 mm
Depth	30 mm
Net weight	18.18 kg
Surface finish	Matt Textured
Colour	White (RAL 9003)

Environment

IK degree of protection	IK10 conforming to EN/IEC 62262
Standards	IEC 61439-1 IEC 61439-2
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.000 cm
Package 1 Width	46.500 cm
Package 1 Length	197.500 cm
Package 1 Weight	19.200 kg
Unit Type of Package 2	PAL

Number of Units in Package 2	10
Package 2 Height	49.000 cm
Package 2 Width	120.000 cm
Package 2 Length	202.000 cm
Package 2 Weight	218.000 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations