Product data sheet
Characteristics

LVS08578

Cover frame, PrismaSeT P, for floor-standing enclosure, 36m, W800, IP30, White, RAL 9003

Green Premium™

Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Cover frame
Range compatibility	PrismaSeT PrismaSeT P cubicle
Provided equipment	Cover frame Wicket door
Enclosure mounting	Floor-standing
Type of door	Cover frame
IP degree of protection	IP30

Complementary

Installation description	Cubicle - width 650 + 150 mm
Door opening angle	120 °
Number of vertical modules [50 mm]	36
Quantity per set	Set of 1
Height	2000 mm
Width	800 mm
Net weight	13.76 kg
Material	Treated sheet steel
Surface finish	Matt Textured
Colour	White (RAL 9003)

Environment

IK degree of protection	IK08 conforming to EN/IEC 62262
Standards	IEC 61439-1 IEC 61439-2
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.500 cm
Package 1 Width	84.500 cm
Package 1 Length	199.000 cm
Package 1 Weight	14.000 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	10
Package 2 Height	89.000 cm
Package 2 Width	120.000 cm
Package 2 Length	202.000 cm
Package 2 Weight	166.000 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Life Is On | Schneider Electric