

Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Rear panel
Range compatibility	PrismaSeT PrismaSeT P enclosure
Device application	Low voltage electrical distribution
Enclosure type	Metal enclosure
Installation description	Cubicle - width 400 mm
Kit composition	Side panel
Standards	IEC 61439-1 for enclosure IEC 61439-2 for enclosure
Product certifications	ASTA

Complementary

Material	Treated sheet steel
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Textured Matt
Colour	White (RAL 9003)
Width	400 mm
Height	2000 mm
Net weight	11.34 kg
Quantity per set	Set of 1





Environment

IP degree of protection	IP55 for enclosure
IK degree of protection	IK10

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	42.000 cm
Package 1 Length	206.500 cm
Package 1 Weight	11.900 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	30
Package 2 Height	75.000 cm
Package 2 Width	120.000 cm
Package 2 Length	206.500 cm
Package 2 Weight	383.000 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Circularity Profile	No need of specific recycling operations
PVC free	Yes