

Product data sheet

Characteristics

LZ1H2X43BD

Ultra compact starter, TeSys Hybrid, 3P, 500VAC, 0.75kW at 400V, 24VDC, Spring terminal



Main

| | |
|-------------------------------------|---|
| Range | TeSys |
| Product name | TeSys Hybrid |
| Device short name | LZ1H |
| Product or component type | Ultra-compact starter |
| Motor starter type | Direct on line |
| Poles description | 3P |
| [Ue] rated operational voltage | 500 V AC |
| [Ie] rated operational current | 2.4 A at 500 V AC-51 2.4 A at 500 V AC-53A 2.4 A at 500 V AC-51 mounting side by side 2.4 A at 500 V AC-53A mounting side by side |
| Thermal protection adjustment range | 0.18...2.4 A |
| Motor power kW | 0.37 KW at 220 V AC 0.65 0.37 KW at 230 V AC 0.65 0.75 KW at 380 V AC 0.65 0.75 KW at 400 V AC 0.65 0.75 KW at 415 V AC 0.65 0.75 KW at 440 V AC 0.65 1.1 kW at 500 V AC 0.65 |
| Motor power hp | 0.5 Hp at 200 V AC 0.5 Hp at 230 V AC 1 hp at 460 V AC |
| [Uc] control circuit voltage | 24 V DC |
| Thermal overload class | Class 10A conforming to IEC 60947-4-2 |

Complementary

| | |
|--|---|
| Auxiliary contact composition | 1 C/O fault signalling |
| Control circuit voltage limits | 19.2...30 V DC |
| Current consumption | <= 40 mA at 24 V DC |
| Reset | Manual Automatic reset Electrical reset |
| Electrical durability | 30 Mcycles |
| Maximum operating rate | 120 Cyc/Mn AC-51 50 % ON 6 cyc/mn AC-53A 50 % ON |
| Mounting mode | By clips |
| Mounting support | DIN rail |
| Connections - terminals | Spring clamp terminals 1 cable(s) 0.2...2.5 mm ² - rigid Spring clamp terminals 1 cable(s) 0.25...2.5 mm ² - flexible - with cable end Spring clamp terminals 1 cable(s) 0.2...2.5 mm ² - flexible - without cable end |
| Certifications | CE CULus |
| Standards | UL 60947-4-1 IEC 60947-4-2 |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Pollution degree | 2 |
| Width | 22.5 mm |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|------------|----------|
| Height | 99 mm |
| Depth | 114.5 mm |
| Net weight | 212 g |

Environment

| | |
|---------------------------------------|------------------------------|
| IP degree of protection | IP20 |
| Protective treatment | TC |
| Ambient air temperature for operation | -25...70 °C without derating |
| Ambient air temperature for storage | -40...80 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.500 cm |
| Package 1 Width | 11.200 cm |
| Package 1 Length | 11.200 cm |
| Package 1 Weight | 240.000 g |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 15.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 2.598 kg |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |