

# Product data sheet

## Characteristics

# MB6-SO-24T

SpaceLogic MB6-SR Ball Valve Actuator, 2 Wire, Spring Return Open, 24VAC/VDC, 6Nm, Rotary, IP31



### Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	MB6
Actuator model	MB6 SRO-24T T31 00
Product destination	Ball valves
Actuator	Rotary
Control type	Electrically operated
Rated supply voltage	24 V AC/DC
Transformer rated power in VA	10 VA
Power consumption in W	2.3 W
Power consumption in VA	3.5 VA AC 1.8 VA DC
Power loss return	Spring return
Control signal	2-position (on/off)
Electrical insulation class	Class III
Tightening torque	53 lb.in 6 N.m
Position indicator	Green push stem with color markers
Additional features	Cable gland fitted for 5-9mm wire OD
Conduit connection	M20
IP degree of protection	IP31
Ambient air temperature for operation	0...76 °C
Relative humidity	5...95 % non-condensing
Ambient air temperature for storage	-40...76 °C
Targeted region	Europe Asia Pacific. Australia.

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.5 kg

### Offer Sustainability

EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations