MCSESU083F2CU0

network switch, Modicon Networking, standard unmanaged, 6 ports for copper with 2 ports for multimode fiber optic





Main

Range of product	Modicon
Product or component type	Ethernet TCP/IP unmanaged switch
Concept	Transparent Ready
Communication port protocol	Ethernet TCP/IP
Port Ethernet	10/100BASE-TX - 6 port(s) copper cable 100BASE-FX - 2 port(s) fiber optic
Maximum number of switches in cascade	Unlimited

Complementary

Integrated connection type	Shielded RJ45 copper cable Duplex SC fiber optic	
Transmission support medium	Twisted shielded pairs cable CAT 5E for copper cable Multimode optical fiber for fiber optic	
Maximum cable distance between devices	100 m copper cable	
Optic fiber length	4 Km 62.5/125 μm 5 km 50/125 μm	
Attenuation	011 DB (62.2/125 μm) 08 dB (50/125 μm)	
[Us] rated supply voltage	1224 V	
Supply voltage limits	9.632 V DC SELV	
Power consumption in W	3.8 W	
Electrical connection	Removable connector 3 ways power supply	
Mounting support	35 mm symmetrical DIN rail	
Marking	CE UL RCM	
Local signalling	1 LED (green) for power supply 1 LED per channel (yellow) for data rate (ETH LINK) 1 dual colour LED (green/yellow) for link status	
Ethernet cabling system	TF switches	
Width	45 mm	
Height	110 mm	
Depth	88 mm	
Net weight	0.235 kg	

Environment

Ambient air temperature for operation	060 °C	
Relative humidity	1095 % non-condensing	
IP degree of protection	IP30	
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility	
Standards	UL 61010-2-201 EN/IEC 61131-2	
Product certifications	CE[RETURN]UL[RETURN]RCM	

Packing Units

0	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.500 cm
Package 1 Width	16.500 cm
Package 1 Length	24.000 cm
Package 1 Weight	375.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.472 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	[☑] End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months

Product data sheet Dimensions Drawings

MCSESU083F2CU0

Dimensions

