



### Main

Range	PowerLogic
Product or component type	Current transducer
Accessory / separate part category	Measurement accessory
Range compatibility	Acti 9 Acti9 iEM3000 iEM3555[RETURN]Acti 9 Acti9 iEM3000 iEM3565[RETURN]PowerLogic PowerLogic EM4200 EM4235[RETURN]PowerLogic PowerLogic EM4200 EM4236[RETURN]PowerLogic PowerLogic EM3500 EM3502A[RETURN]PowerLogic PowerLogic EM3500 EM3550A[RETURN]PowerLogic PowerLogic EM3500 EM3555A[RETURN]PowerLogic PowerLogic EM3500 EM3560A[RETURN]PowerLogic PowerLogic EM3500 EM3561A
Current transformer type	Flexible core

### Complementary

Electrical connection	Flying lead: 2.4 m600 V
Measurement current	50...5000 A
Network frequency	50 Hz
Frequency measurement range	50...1500 Hz
Measurement accuracy	1 %
Installation category	IV
Pollution degree	2
Thickness	8 mm
Height	Opened: 250 mm
Diameter	Closed: 80 mm

### Environment

IP degree of protection	IP67
Standards	UL 61010-1 EN 61010-1 EN 61010-2-032 UL 61010-2-032 ANSI/IEEE C57.13
Product certifications	UL recognized[RETURN]cURus[RETURN]CE
Relative humidity	0...95 %
Ambient air temperature for operation	-15...60 °C
Ambient air temperature for storage	-40...70 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.0 cm
Package 1 Width	30.0 cm
Package 1 Length	39.9 cm
Package 1 Weight	128.18 g
Unit Type of Package 2	S03
Number of Units in Package 2	25

Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.45 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins