

# MF200-230F

MF200 Butterfly Valve Actuator, On/Off or  
3 Position Floating Control, Non-Spring  
Return, 230Vac, 226Nm, SPDT Aux Switch +  
Integrated Heater, IP65

## Main





Product or component type	Actuator
Actuator type	Electric
Actuator product series	MF200
Product destination	Butterfly valves
Actuator	Rotary
Control type	Electrically operated
Switch function	2 SPDT
Rated supply voltage	230 V AC
Feedback signal	0...10 V DC
Hold-in power consumption in W	5 W
Hold-in power consumption in VA	120 VA AC
Power loss return	Non-spring return
Control signal	2-position (on/off) Floating
Tightening torque	2000 lb.in 226 N.m
Additional features	Heater
Leads and connections	Terminal block
Spring return timing	36 s
IP degree of protection	IP65
Material	PTFE (polytetrafluoroethylene): seal
Duty cycle	25 %
Ambient air temperature for operation	-25...65 °C
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-40...65 °C
Targeted region	Europe Asia Pacific. Australia.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.0 cm
Package 1 Width	31.0 cm
Package 1 Length	36.0 cm
Package 1 Weight	13.0 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations