

MF40-24F

Act: Elec, 3P Float, SR, 24 VAC/VDC, 40 Nm,
Rotary, SPDT, IP54

Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	MF40
Actuator model	MF40-24F T54 00
Product destination	Butterfly valves
Actuator	Rotary
Control type	Electrically operated
Switch function	2 SPDT (optional)
Rated supply voltage	24 V AC/DC
Power consumption in W	4 W
Power consumption in VA	6 VA AC
Hold-in power consumption in W	2 W
Power loss return	Stay in place
Control signal	2-position (on/off) Floating
Electrical insulation class	Class III
Tightening torque	354 lb.in 40 N.m
Position indicator	Stroke indicator on bracket
Leads and connections	Terminal block
IP degree of protection	IP54
Ambient air temperature for operation	0...50 °C
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.2 cm
Package 1 Width	17.2 cm
Package 1 Length	23.7 cm
Package 1 Weight	2.248 kg

Offer Sustainability

EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations