

Product data sheet

Characteristics

MF40ER-24M

MF40-ER Butterfly Valve Actuator, Modulating, 2-10VDC, 24Vac/dc, 40Nm, Electronic Return, IP54



Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	MF40ER
Actuator model	MF40ER-24M
Product destination	Butterfly valves
Actuator	Rotary
Control type	Electrically operated
Feedback signal	2...10 V DC
Power consumption in W	11 W
Hold-in power consumption in W	3 W
Power loss return	Spring return
Control signal	Proportional/modulating
Electrical insulation class	Class II
Tightening torque	354 lb.in 40 N.m
Position indicator	Stroke indicator on bracket
Lead length	1.5 m
IP degree of protection	IP54
Material	Reinforced teflon: seal EPDM: O-rings
Ambient air temperature for operation	0...50 °C
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.0 cm
Package 1 Width	19.0 cm
Package 1 Length	29.0 cm
Package 1 Weight	2.81 kg

Offer Sustainability

EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
RoHS exemption information	<input checked="" type="checkbox"/> Yes
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
Circularity Profile	No need of specific recycling operations