

MF68-24M

MF68 Butterfly Valve Actuator, Modulating,
0-10Vdc or 2-10Vdc, Non-Spring Return,
24Vac, 68Nm, SPDT Aux Switch + Integrated
Heater, IP65

Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	MF68
Product destination	Butterfly valves
Actuator	Rotary
Switch function	2 SPDT
Rated supply voltage	24 V AC
Feedback signal	0...10 V DC
Power loss return	Non-spring return
Control signal	Proportional/modulating
Tightening torque	601 lb.in 68 N.m
Leads and connections	Terminal block
IP degree of protection	IP65
Material	Reinforced teflon: seal EPDM: O-rings
Ambient air temperature for operation	-29...65 °C
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-40...65 °C
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.0 cm
Package 1 Width	29.0 cm
Package 1 Length	32.0 cm
Package 1 Weight	6.0 kg

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes