## Product data sheet Characteristics

# MR90NC-230T THERMO ACTUATOR 230V NC



#### Main Product or component Actuator type Actuator type Thermoelectric MR90 Actuator product series MR90NCD-230T-2M 43 00 Actuator model Product destination Thermostatic radiator valves Actuator Linear Control type Manual override with 5/32 allen wrench Power consumption in 50 VA AC Hold-in power 1.8 VA AC consumption in VA Control signal 2-position (on/off) Stroke length 4 mm Stroke auto calibration False Force N 396 N 89 lbf Force lbf Position indicator Green push stem with color markers Lead length 2 m Bipolar Leads and connections Ambient air temperature 2...50 °C for operation -45...50 °C Ambient air temperature

Europe

### **Packing Units**

| . doming of mo               |         |  |
|------------------------------|---------|--|
| Unit Type of Package 1       | PCE     |  |
| Number of Units in Package 1 | 1       |  |
| Package 1 Height             | 9.0 cm  |  |
| Package 1 Width              | 9.0 cm  |  |
| Package 1 Length             | 12.0 cm |  |
| Package 1 Weight             | 100.0 g |  |
|                              |         |  |

for storage
Targeted region

## Offer Sustainability

| EU RoHS Directive          | Compliant EPEU RoHS Declaration |  |
|----------------------------|---------------------------------|--|
| Toxic heavy metal free     | Yes                             |  |
| Mercury free               | Yes                             |  |
| China RoHS Regulation      | ☑ China RoHS Declaration        |  |
| RoHS exemption information | ₫Yes                            |  |
| Environmental Disclosure   | Product Environmental Profile   |  |