



Main

Range	KNX
Product or component type	Presence detector
Bus type	KNX
Colour tint	Polar white

Complementary

Device presentation	Complete product
Number of channels	5
Protection type	Creep zone protection
Type of setting	Light sensitivity adjustable
Duty cycle	15300 minutes
Time delay range	0...1 s (switch-on)
Detection face	Lateral: 7 m
Detection angle	360° horizontal
Device mounting	Flush
Mounting height	2.5 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.100 cm
Package 1 Width	14.400 cm
Package 1 Length	18.000 cm
Package 1 Weight	186.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	20.100 cm
Package 2 Width	30.500 cm
Package 2 Length	40.500 cm
Package 2 Weight	1.482 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Silicon free	Yes
Contractual warranty	
Warranty	18 months