



Main

Range of product	KNX
Product or component type	Heating actuator
Operating mode	Manual KNX bus system
Bus type	KNX
Rated output	0.5 A - 5 x for output continuous 0 to 100 % 0.5 A for output switching on/off
Rated input	Signal voltage (SELV): 2 x binary

Complementary

Total number of 18 mm modules	4
Wiring device mounting	DIN rail
[Ue] rated operational voltage	207...253 V
Load type	Valve: 230 V AC Valve: 24 V AC

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.100 cm
Package 1 Width	12.600 cm
Package 1 Length	15.900 cm
Package 1 Weight	332.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	19.700 cm
Package 2 Width	30.600 cm
Package 2 Length	41.000 cm
Package 2 Weight	3.688 kg

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------