



### Main

Range of product	KNX
Product or component type	Switch actuator
Operating mode	Manual
Bus type	KNX
Modular device additional info	Connectable with different phases
Number of contacts	4

### Complementary

Function available	Current detection
Total number of 18 mm modules	4
Mounting support	DIN rail
[Ue] rated operational voltage	230 V
Network frequency	50...60 Hz
[In] rated current	0.1...16 A
Load type	Incandescent lamps: <= 3600 W, 230 V AC Halogen lamps: <= 2500 W, 230 V AC Parallel compensated fluorescent lamp: <= 2500 VA, 230 V AC Capacitive: , 16 A, 200 µF, 100...240 V AC Motor: <= 1000 W, 230 V AC

### Environment

IP degree of protection	IP20
-------------------------	------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.100 cm
Package 1 Width	13.600 cm
Package 1 Length	15.900 cm
Package 1 Weight	372.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	19.700 cm
Package 2 Width	30.600 cm
Package 2 Length	40.400 cm
Package 2 Weight	4.106 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------