



Main

Range of product	KNX
Product or component type	Switch actuator
Operating mode	Manual
Bus type	KNX
Modular device additional info	Connectable with different phases
Number of contacts	8

Complementary

Function available	Current detection
Total number of 18 mm modules	8
Mounting support	DIN rail
[Ue] rated operational voltage	100...240 V
Network frequency	50...60 Hz
[In] rated current	0.1...16 A
Load type	Incandescent lamps: ≤ 3600 W, 230 V AC Halogen lamps: ≤ 2500 W, 230 V AC Incandescent lamps: ≤ 1600 W, 100 V AC Incandescent lamps: ≤ 3840 W, 240 V AC Halogen lamps: ≤ 1086 W, 100 V AC Halogen lamps: ≤ 2608 W, 240 V AC Parallel compensated fluorescent lamp: ≤ 1086 VA, 100 V AC Parallel compensated fluorescent lamp: ≤ 2500 VA, 230 V AC Parallel compensated fluorescent lamp: ≤ 2608 VA, 240 V AC Capacitive: , 16 A, 200 μF, 100...240 V AC Motor: ≤ 434 W, 100 V AC Motor: ≤ 1000 W, 230 V AC Motor: ≤ 1043 W, 240 V AC

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.200 cm
Package 1 Width	12.600 cm
Package 1 Length	28.000 cm
Package 1 Weight	718.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	19.500 cm
Package 2 Width	30.700 cm
Package 2 Length	40.200 cm
Package 2 Weight	4.686 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------