Product data sheet Characteristics

MTN6500-0103

SpaceLogic KNX IP Router DIN Rail





Main

Range of product SpaceLogic KNX Range SpaceLogic KNX Product or component type Bus type KNX Market segment Commercial Residential		
Product or component type Bus type KNX Market segment Commercial	Range of product	SpaceLogic KNX
Bus type KNX Market segment Commercial	Range	SpaceLogic KNX
Market segment Commercial	•	IP router
	Bus type	KNX
	Market segment	

Complementary

Function available	Supports KNX Secure	
Material	PC	
Control type	2 push-buttons	
Local signalling	3 LEDs	
Software type	Updateable software	
Communication network type	Ethernet RJ45	
Communication port protocol	Ethernet TCP/IP KNX UDP/IP KNX IP security KNX data security KNX long frame ARP ICMP IGMP V2	
Transmission rate	10/100 Mbit/s	
Connections - terminals	Ethernet: RJ45 connector KNX: BUS	
Total number of 18 mm modules	1	
Mounting support	DIN rail	
[Ue] rated operational voltage	24 V	

Environment

Relative humidity	593 %	
Ambient air temperature for storage	-2570 °C	
Ambient air temperature for operation	-545 °C	
Standards	EMC directive	
	EN 50491-3	
	EN 50491-5-2	
	EN 50491-5-3	
	EN 61000-6-2	
	EN 61000-6-3	
	EN 50581 : 2012	
IP degree of protection	IP20	

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0 cm
Package 1 Width	7.0 cm
Package 1 Length	9.5 cm
Package 1 Weight	90.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	60
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	6.03 kg

Offer Sustainability

Green Premium product	
☑ REACh Declaration	
Compliant with Exemptions	
[™] China RoHS Declaration	
₫Yes	
Product Environmental Profile	
☑ End Of Life Information	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	