



Main

Range of product	SpaceLogic KNX
Range	SpaceLogic KNX
Product or component type	IP interface device
Bus type	KNX
Market segment	Commercial Residential

Complementary

Function available	Supports KNX Secure
Material	PC
Control type	2 push-buttons
Local signalling	3 LEDs
Software type	Updateable software
Communication network type	Ethernet RJ45
Communication port protocol	Ethernet TCP/IP KNX UDP/IP KNX IP security KNX data security KNX long frame ARP ICMP IGMP V2
Transmission rate	10/100 Mbit/s
Connections - terminals	Ethernet: RJ45 connector KNX: BUS
Total number of 18 mm modules	1
Mounting support	DIN rail
[Ue] rated operational voltage	24 V

Environment

Relative humidity	5...93 %
Ambient air temperature for storage	-25...70 °C
Ambient air temperature for operation	-5...45 °C
Standards	EMC directive EN 50491-3 EN 50491-5-2 EN 50491-5-3 EN 61000-6-2 EN 61000-6-3 EN 50581 : 2012
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0 cm
Package 1 Width	7.0 cm
Package 1 Length	9.5 cm
Package 1 Weight	86.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	60
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.984 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins