



## Main

|                           |                |
|---------------------------|----------------|
| Range of product          | Spacelogic KNX |
| Product or component type | Power supply   |
| Bus type                  | KNX            |
| Topology                  | TP256          |
| Provided equipment        | Line choke     |
| Colour                    | White          |

## Complementary

|                                |  |
|--------------------------------|--|
| Total number of 18 mm modules  | 6  |
| Mounting support               | DIN rail   |
| Rated voltage                  | 180...264 V AC 50...60 Hz  |
| Maximum power consumption in W | 6.4 W  |
| Maximum short-circuit current  | 3 A  |
| Maximum output current         | 1280 mA  |
| Output voltage                 | 30 V DC  |
| Power supply type              | SELV   |
| Local signalling               | LED  |
| Connections - terminals        | 0.5...4 mm <sup>2</sup> screw terminal for solid cable<br>0.5...4 mm <sup>2</sup> screw terminal for stranded cable<br>0.5...2.5 mm <sup>2</sup> screw terminal for stranded with sleeve cable |
| Height                         | 90 mm  |
| Width                          | 108 mm   |
| Depth                          | 65 mm  |

## Environment

|                                       |  |
|---------------------------------------|--|
| Ambient air temperature for operation | -5...45 °C                                 |
| Ambient air temperature for storage   | -25...70 °C                                |
| Relative humidity                     | 93 % non-condensing                        |
| Operating altitude                    | 2000 m                                     |
| Directives                            | 89/336/EEC - electromagnetic compatibility |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 8.0 cm  |
| Package 1 Width              | 12.5 cm |
| Package 1 Length             | 16.0 cm |
| Package 1 Weight             | 506.0 g |
| Unit Type of Package 2       | S04     |
| Number of Units in Package 2 | 22      |
| Package 2 Height             | 30.0 cm |

|                  |           |
|------------------|-----------|
| Package 2 Width  | 40.0 cm   |
| Package 2 Length | 60.0 cm   |
| Package 2 Weight | 12.004 kg |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>   |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |