

# Product data sheet

## Characteristics

# MTN6513-1203

Power supply, Spacelogic KNX, REG-K/320 mA, white



### Main

Range of product	SpaceLogic KNX
Product or component type	Power supply
Bus type	KNX
Topology	TP256
Provided equipment	Line choke
Colour	White

### Complementary

Total number of 18 mm modules	4
Mounting support	DIN rail
Rated voltage	180...264 V AC 50...60 Hz
Maximum power consumption in W	1.8 W
Maximum short-circuit current	1 A
Maximum output current	320 mA
Output voltage	30 V DC
Power supply type	SELV
Local signalling	LED
Connections - terminals	0.5...4 mm <sup>2</sup> screw terminal for solid cable 0.5...4 mm <sup>2</sup> screw terminal for stranded cable 0.5...2.5 mm <sup>2</sup> screw terminal for stranded with sleeve cable
Height	90 mm
Width	72 mm
Depth	65 mm

### Environment

Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	93 % non-condensing
Operating altitude	2000 m
Directives	89/336/EEC - electromagnetic compatibility

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.000 cm
Package 1 Width	12.000 cm
Package 1 Length	15.700 cm
Package 1 Weight	342.000 g
Unit Type of Package 2	S04
Number of Units in Package 2	28
Package 2 Height	30.000 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	10.315 kg
Unit Type of Package 3	P12
Number of Units in Package 3	112
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	52.556 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 Yes
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins